







DRAWING IN THIRD ANGLE PROJECTION

SPECIFICATIONS

CAPACITY (Nm)	70
OVERLOAD CAPACITY (%F.S.)	300
DIFFERENTIAL OUTPUT @ F.S. (V)	2.5±2
POWER SUPPLY (V)	4.5V-5V, 25MA
BRIDGE RESISTANCE (Ω) NOMINAL	350
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-20 TO +85
CROSSTALK (%F.S.)	1.0
AXIAL FORCE FOR CROSSTALK (N)	140
RADIAL FORCE FOR CROSSTALK (N)	280
BENDING MOMENT FOR CROSSTALK (Nm)	10
TORSION ANGLE (CALCULATED)	0.04°
TORSIONAL STIFFNESS (KNm/RAD)	100
BENDING STIFFNESS (KNm/RAD)	11
MASS (KG)	0.16

WIRING CODE

COLOR	FUNCTION
RED	+EX
GREEN	+SIG
BLACK	GND
BROWN	-SIG

SUNRISE INSTRUMENTS

www.srisensor.com

SINGLE AXIS TORQUE LOADCELL
D81.5MM, 70 Nm

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MM

M2212W2

REV.
0.1