




POSITIVE OUTPUT IS EXPECTED WHEN LOAD (FORCE OR MOMENT) IS APPLIED TO THE TOOL SIDE PER COORDINATE SYSTEM AS SHOWN

ALL CHANNELS ARE STRUCTURALLY DECOUPLED. NO DECOUPLING ALGORITHM REQUIRED. STANDARD DATA ACQUISITION SYSTEM CAN BE USED

IP PROTECTION: IP60. USE PART # "M3935MP" FOR IP68 (10M) VERSION

	Fx	Fy	Fz	Mx	My	Mz
CAPACITY (N/Nm)	5400	5400	10800	540	540	432
OUTPUT (mV/V)	2.9	2.9	0.7	1.7	1.7	1.9
BRIDGE RES. (Ω)	350	350	350	350	350	700

WIRING CODE - TWISTED PAIR

FUNC	FX	FY	FZ	MX	MY	MZ
+SIG	WHITE(BROWN)	ORG(BROWN)	BLUE(BROWN)	YEL(BROWN)	RED(BROWN)	WHITE(BLACK)
-SIG	BROWN(WHITE)	BROWN(ORG)	BROWN(BLUE)	BROWN(YEL)	BROWN(RED)	BLACK(WHITE)
+EXC	ORG(BLACK)	BLACK(ORG)	BLUE(BLACK)	BLACK(BLUE)	RED(BLACK)	BLACK(RED)
-EXC	YELLOW(BLACK)			BLACK(YELLOW)		

"YEL"="YELLOW", "ORG"="ORANGE", "WHITE(BROWN)" = WHITE CABLE IN WHITE/BROWN PAIR

SPECIFICATIONS

EXCITATION MAX. (V)	15
OVERLOAD CAPACITY (%F.S.)	150
FREE AIR RESONANT FREQ. (HZ.)	3300
CROSSTALK (%F.S.)	5.0
NON-LINEARITY (%F.S.)	1.0
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE (°C)	-40 TO +100
MASS (KG)	1.95

SUNRISE INSTRUMENTS

www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
D135MM F5400N

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MM

M3935M

REV.
A