




POSITIVE OUTPUT IS EXPECTED WHEN LOAD (FORCE OR MOMENT) IS APPLIED TO THE TOOL SIDE PER COORDINATE SYSTEM AS SHOWN

ALL CHANNELS ARE STRUCTURALLY DECOUPLED. NO DECOUPLING ALGORITHM REQUIRED. STANDARD DATA ACQUISITION SYSTEM CAN BE USED

IP PROTECTION: IP68

	F _x	F _y	F _z	M _x	M _y	M _z
CAPACITY (N/Nm)	9000	9000	18000	900	900	700
OUTPUT (mV/V)	2.2	2.2	0.8	2.1	2.1	2.1
BRIDGE RES. (Ω)	350	350	350	350	350	700

WIRING CODE - TWISTED PAIR

FUNC	FX	FY	FZ	MX	MY	MZ
+SIG	WHITE(BROWN)	ORG(BROWN)	BLUE(BROWN)	YEL(BROWN)	RED(BROWN)	WHITE(BLACK)
-SIG	BROWN(WHITE)	BROWN(ORG)	BROWN(BLUE)	BROWN(YEL)	BROWN(RED)	BLACK(WHITE)
+EXC	ORG(BLACK)	BLACK(ORG)	BLUE(BLACK)	BLACK(BLUE)	RED(BLACK)	BLACK(RED)
-EXC	YELLOW(BLACK)			BLACK(YELLOW)		

"YEL"="YELLOW", "ORG"="ORANGE", "WHITE(BROWN)" = WHITE CABLE IN WHITE/BROWN PAIR

SPECIFICATIONS

EXCITATION MAX. (V)	15
OVERLOAD CAPACITY (%F.S.)	150
FREE AIR RESONANT FREQ. (HZ.)	4100
CROSSTALK (%F.S.)	5
NON-LINEARITY (%F.S.)	1.0
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE (°C)	-40 TO +100
IP PROTECTION	IP60
MASS (KG)	2.9

SUNRISE INSTRUMENTS
www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
D135MM F9000N, IP68

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MM

M3945P2

REV.
0.1